

# Conwed Fibers® Hydro Mulch® 2000

## Wood Fiber with Tackifier

Provides protection on difficult sites and conditions!

- Conwed Fibers® Thermally Refined® wood fibers utilize heat and pressure to break wood down into more fibrous material with greater surface area. This results in greater yield, higher water retention and increased productivity, which lowers project costs
- Hydro Mulch® 2000 has a premium organic guar tackifier that is pre-blended within the wood fiber, which ensures enhanced coverage
- Eliminates the extra step and mess of field mixing
- Guar gum tackifier enhances the chemical bond within the mulch matrix for better erosion control
- Disperses quickly in water, which allows for better blending with seed and fertilizer
- Ideal protection for critical slopes and sites where weather calls for an extra measure of protection
- Thermally Refined wood fibers holds up to 50% more water than competitors products – creating an excellent environment for seed germination
- Non-toxic and environmentally safe
- Maximum slope length of 30 feet
- Use approved mechanically agitated equipment for optimum pumping and application performance
- Hydro Mulch 2000 functional longevity is  $\leq 3$  months



### Product Composition:

Thermally Refined® Wood Fibers – 85%  $\pm$  3%  
 Guar Based Tackifier – 3%  $\pm$  1%  
 Moisture Content – 12%  $\pm$  3%

(40) 50-lb bales per pallet

#### Slope Gradient/Condition

$\leq 4H:1V$   
 $> 4H:1V$  and  $\leq 3H:1V$   
 $> 3H:1V$  and  $\leq 2H:1V$

#### Rate

2000 lb/acre  
 2500 lb/acre  
 3000 lb/acre

